

HOME CARE DAMP PROOF BASE COAT



PRODUCT DESCRIPTION

Macaw Home Care Damp Proof Base Coat is a specially formulated product consisting of penetrative polymer that binds with the surface giving better resistance to dampness. Its triple booster formulation fights against dampness, efflorescence and alkalinity, at the same time acts as a superior undercoat for topcoat application. It is suitable for both interior and exterior surfaces.



PRODUCT FEATURES



ALKALI AND SALT RESISTANT

Gives resistance to deterioration that occurs due to reaction with alkaline chemicals



PROTECTION FROM DAMPNESS

It does not allow moisture and any kind of water seepage to enter the masonry surface

ASPECT

WHITE VISCOUS LIQUID

TOXICITY



Non-toxic with low VOC



COVERAGE: (Approx)

Forced coverage
30 ft²/Ltr/2 Coats

AVAILABLE PACKS



20 ltr



10 ltr



4 ltr



1 ltr

HOME CARE DAMP PROOF BASE COAT



DIRECTIONS FOR APPLICATION

Application Method




Brush/Roller/
Spray Gun

Dilution Ratio



Dilution Ratio: Add 300-400 ml
of potable water/L

Recommended Undercoat



Macaw Home Care Damp
Proof Base Coat

Drying Time



4-6 Hours

*Drying time may vary as per
weather conditions

DIRECTIONS FOR USE

SURFACE PREPARATION AND APPLICATION:



- New masonry surfaces must be allowed to cure completely
- Typical curing time for masonry surfaces is 28 days
- Ensure that the surface is completely free from all dirt, loosely held plaster, powdery residue, dust, oil, grease or any other contaminations
- Remove growth of fungus, algae or moss by vigorous wire brushing/pressure spray machine and clean with water
- For previously painted surface, strip off the loose particles from the surface
- Dilute the paint 30-40% by volume with potable water, and apply by brush/roller/spray gun
- Recoat after 8 hours (recoat time may vary depending upon climatic conditions of different places)

IMPORTANT NOTES



- Shake well before use and do not over dilute
- Keep the container tightly closed after use
- Keep away from children and edibles, prevent direct eye contact; rinse with clean water and seek medical help if necessary
- Do not apply during rain, fog or mist or when the temperature falls below 10 °C
- It is always advised to keep the materials away from direct sunlight for a prolonged period

SHELF LIFE

Up to 36 months if kept in sealed containers in shade, away
from direct sunlight

USAGE AREA

On plastered/puttied surfaces

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION.

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

