

HOME CARE DAMP PROOF ELASTO



PRODUCT DESCRIPTION

Macaw Home Care Damp Proof Elasto is a fibre-reinforced liquid applied elastomeric water proofing membrane, specially formulated product consisting of penetrative polymer that binds with the surface giving better resistance to dampness. Its triple booster formulation fights against dampness, efflorescence and alkalinity, at the same time acts as a superior undercoat for topcoat application. It is suitable for exterior surfaces.



PRODUCT FEATURES



EASY TO USE

Single component, user-friendly water-based product



TO BE USED AS PRIMING COAT

Use as a primer with priming coat



WATER PERMEABILITY

Resistance towards ingress of water



HIGHER COVERAGE

The product has higher coverage than other home care products



ADHESION

Strong adhesion to masonry surfaces



LOWER SMELL

Odorless paint, which eliminates immediate paint smell and gives a pleasant painting experience



ALKALI AND SALT RESISTANT

Gives resistance to deterioration that occurs due to reaction with alkaline chemicals



IMPROVED WHITENESS

A better whiteness is obtained through better spacing for improved light scattering

FINISH

SMOOTH MATT

ASPECT

SMOOTH VISCOUS PASTE

TOXICITY



Non-toxic with low VOC

AVAILABLE PACKS



20 ltr



10 ltr



4 ltr



1 ltr

HOME CARE DAMP PROOF ELASTO



DIRECTIONS FOR APPLICATION

PRIMING: Priming is essential for all types of applications- Vertical & Horizontal

HORIZONTAL WATERPROOFING

Product	Stage	Dilution	Coverage (ft ² /Ltr/2 Coats)	Application Tool	Inter-coat Period
DAMP PROOF ELASTO	As primer coat	30-40% (max) with potable water		Brush	4-6 Hrs
DAMP PROOF ELASTO	Waterproofing 1 st coat		30	Brush/ Roller	4-6 Hrs
DAMP PROOF ELASTO	Waterproofing 2 st coat			Brush/ Roller	4-6 Hrs

SURFACE PREPARATION AND APPLICATION

- New masonry surfaces must be allowed to cure completely
- Typical curing time is 28 days
- Ensure that the surface is completely free from all dirt, loosely held plaster, powdery residue, dust, oil, grease or any other contaminations
- Remove growth of fungus, algae or moss by vigorous wire brushing and cleaning with water

FOR PREVIOUSLY PAINTED SURFACE

- Strip off the loose particles from the surface
- Dilute the paint 30-40% by volume with potable water, and apply by brush/roller
- Recoat after 8 hours (recoat time may vary depending upon climatic conditions of different places)

DIRECTIONS FOR APPLICATION

IMPORTANT NOTES

- Shake well before use and do not over dilute
- Keep the container tightly closed after use
- Keep away from children and edibles, prevent direct eye contact; rinse with clean water and seek medical help if necessary
- Do not apply during rain, fog or mist or when the temperature falls below 10 °C
- It is always advised to keep the materials away from direct sunlight for a prolonged period

SHELF LIFE: Up to 36 months if kept in sealed containers in shade, away from direct sunlight

USAGE AREA: On plastered/puttied surfaces

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION.

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

