

HOME CARE PU ROOF & WALL COAT



PRODUCT DESCRIPTION

Macaw Home Care PU COAT is a one component liquid waterproofing paint for Roof/Wall, which while applied forms a protective heat-resistant membrane. It is eco-friendly, highly elastic and UV-resistant layer, ensuring long-lasting protection.

PRODUCT FEATURES



WATERPROOFING MEMBRANE

It prevents leaks and damages caused because of water seepage and makes roofs and exterior walls waterproof



HIGHLY ELASTIC

Protects integrity of masonry surfaces



CRACK BRIDGING

Seals cracks on roofs and walls



UV RESISTANT

Breathable coating withstands exposure to sunlight and protects roofs and walls



EXCELLENT ADHESION

It is used as a primer by diluting water and applied on porous and non-porous surface

FINISH

SMOOTH AND UNIFORM

TOXICITY

Non-toxic

AVAILABLE PACKS



20 ltr



10 ltr



4 ltr



1 ltr



HOME CARE PU ROOF & WALL COAT



DIRECTIONS FOR APPLICATION

Application Method



Brush/Roller

Dilution Ratio



50% dilution with potable water

Drying Time



4-6 Hours

*Drying time may vary as per weather conditions

SURFACE PREPARATION



- All kinds of masonry surfaces, new or old, must be allowed to be cured completely
- Ensure that the surface is completely free from all types of dirt, loose particles, algae and fungus through wire brushing and thoroughly cleaning with water
- Fill cracks up to 5 mm with Macaw Crack fillers and bigger cracks with Macaw Latex Plus modified repair mortar
- Make the surface dry before application

APPLICATION PROCESS

Horizontal/Roof Application

Priming- Dilute Macaw Home Care PU Coat with 50% of potable water and apply as priming coat. Continuous stirring is required while mixing and recommended drying time is 4-6 hours.

Waterproof Coating- Apply 2 undiluted coats with an interval of 4-6 hours.

Vertical/Wall Application

Priming- Dilute Macaw Home Care PU Coat with 50% of potable water and apply as priming coat. Continuous stirring is required while mixing and recommended drying time is 4-6 hours.

Waterproof Coating- Apply 1 coat, 25% dilution with proposed drying time of 4-6 hours. Must apply desired exterior topcoat (2 coats) as per suggested dilution.

IMPORTANT NOTES



- Prior to use, shake the container well
- Do not over dilute
- Keep the container tightly closed after use
- Strain the materials through fine sieve before use
- Keep away from children and edibles, prevent direct eye contact; rinse with clean water and seek medical help if necessary

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION.

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM



SHYAM STEEL
SINCE 1953