

TruGlow[★]

Hi-Gloss

Premium Enamel



PRODUCT DESCRIPTION

TruGlow Hi-Gloss is a high-quality, solvent-based premium enamel. It provides protection to multiple interior and exterior surfaces.

PRODUCT FEATURES



HIGH GLOSS

Gloss of $80 \pm 5^\circ$ at 60° GH on tin plate when released (It varies with shades; measured as per standard test methods)



EASY TO APPLY

TruGlow Hi-Gloss offers a hassle-free application with effortless usage as it can be easily diluted and applied to multiple surfaces with brush/roller/spray



HIGHER COVERAGE

The coverage is 90-120 sq.ft./L/2 coats that may vary based on factors such as surface condition, dilution and other variables



FLAMMABLE

The paint is an inflammable liquid and needs to be handled with care

COLOUR RANGE

Colours as per industry standard
(Refer Macaw shade card)

FINISH

HIGH GLOSS

AVAILABLE PACKS



10 Ltr



4 Ltr



1 Ltr



500ml



TruGlow[®]

Hi-Gloss

Premium Enamel



DIRECTIONS FOR APPLICATION

Application Method



Brush/Roller/Spray

Dilution Ratio



Dilute with MTO to the standard dilution up to 10-15% by volume

Recommended Undercoat



Macaw Red Oxide Metal Primer for iron surface

Solvent-based primer according to surfaces

Drying Time



Surface Dry: 3-4 hours

Hard Dry: Overnight, depending on surface and weather conditions

SURFACE PREPARATION AND APPLICATION

- Sand the surface with coarse sand/Emery paper according to the type of the surface, to remove rust, dust, grease and loose particles

PRIMING

- After surface preparation, apply a coat of suitable primer according to the surface and allow sufficient drying time
- Sand the surface lightly with less coarse sand/Emery paper and wipe clean with a dry cloth

TOPCOAT

- Prior to application, dilute the paint with MTO to the standard dilution up to 10-15% by volume, if required
- Apply 2 coats of TruGlow Hi-Gloss Premium Enamel for best outcome
- Keep 8 hours of drying time between coats

IMPORTANT NOTES



- Store safely and away from flammable sources
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required
- Store away from edibles

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

