

AMENDO

Wood Primer



PRODUCT DESCRIPTION

Amendo Wood Primer is designed for wood and its by-products. It offers a resilient and sturdy film, formulated with a special type of synthetic alkyd binder and various additives.

SURFACE PREPARATION AND APPLICATION



- Prior to application of Amendo Wood Primer, ensure the surface is clean and there is no dust
- Level the surface with a suitable sandpaper
- If required, wipe clean with MTO and ensure the surface is completely dry
- Use MTO for dilution up to 10-12% by volume
- Before paint application, apply 1-2 coats of Amendo Wood Primer
- Leave it to dry for approximately 6-8 hours in normal weather condition before application of subsequent coats
- The wood primer can be applied by brush or spray

RECOMMENDED SURFACE



Wooden Surfaces

AVAILABLE PACKS



10 ltr



4 ltr



1 ltr



500ml



AMENDO

Wood Primer



RECOMMENDED SURFACE

Wooden surfaces and wood by-products

TECHNICAL DATA

Product Type	Primer
Finish	Matt
Thinner	MTO
Method of Application	Brush and spray
Recommended Application Viscosity	Brushing viscosity must be 60-65 sec at 30°C in Ford Cup B4 and in case of spray application, it must be 40-45 sec at 30°C in Ford Cup B4 at a pressure 40-45 psi
Coverage	70-80 sq.ft./L/1 coat (by brush on normal, properly cured wooden surface)
Dilution	10-12% by volume
Drying Time	Surface Dry: 2-3 hrs depending on ambient conditions Hard Dry: 6-8 hrs depending on ambient conditions Overcoating must be kept overnight for drying
No. of Coats	As per requirement
Flash Point	Above 30°C
Pot Life	Use mixed material within 4-6 hrs. For partly used material, put a little MTO on top layer of primer and keep it tightly closed. This prevents skinning and loss of primer
Colour	White, Pink
Safety Data	Refer MSDS

*The coverage may vary based on several factors such as surface conditions, preparation, application skill, weather and dilution. The mentioned coverage is an estimate for ideal conditions and may differ based on site-specific factors.

IMPORTANT NOTES



- Shake the container and stir well before use; do not over dilute
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required
- Store away from edibles

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/II, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback / complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

