

DURA FILL

Interior Primer



PRODUCT DESCRIPTION

Dura Fill Interior Primer provides good adhesion and improves durability of paint for topcoat application.

PRODUCT FEATURES



SEALS PORES AND BETTER ADHESION

It reduces porosity of the surface, provides better adhesion and coverage for topcoat

TOXICITY



- Eco-friendly product with no added lead, mercury and chromium
- Low VOC

COVERAGE (APPROX)



100-110 sq.ft./L/1coat

- Coverage may depend on factors like surface conditions, surface preparations, application skills, weather conditions, dilution, etc.

FINISH

SMOOTH

AVAILABLE PACKS



20 Ltr



10 Ltr



4 Ltr



1 Ltr



DURA FILL

Interior Primer



DIRECTIONS FOR APPLICATION

Application Method



Brush/Roller/Spray

Dilution Ratio




Dilute 1L of primer with potable water (up to 1L/100%) depending on required consistency

Drying Time



Keep 4 hours interval between two subsequent coats; allow complete drying of paint

SURFACE PREPARATION AND APPLICATION



- Before application ensure the surface is free from loose particles and dirt. Use suitable sandpaper to rub the surface
- Wipe clean with dry cloth and ensure the surface is completely dry
- Apply a coat of Dura Fill Interior Primer after diluting it to the standard dilution up to 100% by volume, and allow minimum 4 hours drying time
- Apply another coat of primer after applying Flexi Strong Acrylic Wall Putty and allow sufficient drying time
- Dura Fill Interior Primer can be applied by brush, roller or spray

IMPORTANT NOTES



- Prior to use, shake the container well
- Ideal moisture content of the wall should be below 12%
- The perfect pH value of the exterior wall must be between 7-11
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

