

FLEXI STRONG

ACRYLIC WALL PUTTY



PRODUCT DESCRIPTION

Flexi Strong Acrylic Wall Putty is a water-based, ready-to-use putty that provides a robust and seamless foundation for flawless paint application. It has a smooth finish and effectively conceals hairline cracks, bends and joints.

PRODUCT FEATURES



NO CHALKING

It helps to avoid any formation of powdery substances



NO CRACKING

Its flexibility protects the wall from any cracking, flaking or peeling



SMOOTH FINISH

Makes the uneven wall perfectly smooth for primer application

TOXICITY



- Eco-friendly product with no added lead, mercury and chromium
- Low VOC

COVERAGE (APPROX)

10-20 sq.ft./Kg/2 coats

- Coverage may depend on factors like surface conditions, surface preparations, application skills, weather conditions, dilution, etc.

AVAILABLE PACKS



20kg



10kg



5kg



2kg



FLEXI STRONG

ACRYLIC WALL PUTTY



DIRECTIONS FOR APPLICATION

Application Method



Putty Knife

Dilution Ratio



Add potable water if required

Recommended Undercoat




Amendo Interior Primer
or
Dura Fill Interior Primer

Drying Time



Keep 4-6 hours interval between two subsequent coats; allow complete drying of paint

SURFACE PREPARATION AND APPLICATION



- For previously painted surfaces, remove loose paint, dust and grease using wire brush/Emery paper
- For new surfaces, before application of putty, ensure the surface is completely clean and cured
- Wipe clean with dry cloth and ensure the surface is completely dry
- In case of dents and holes, use Flexi Strong Acrylic Wall Putty with fine sand in the ratio of 1:3; keep 4-6 hours of drying time
- Apply Amendo Interior/Dura Fill Interior Primer on the surface, and allow minimum 4 hours drying time
- Apply Flexi Strong Acrylic Wall Putty using putty knife to cover hairline cracks and uneven surfaces; allow it to dry completely
- Sand the surfaces with Emery paper for smoothening
- If required, apply another coat of Flexi Strong Acrylic Wall Putty and allow it to dry
- Before topcoat application, apply another coat of primer and allow sufficient drying time

IMPORTANT NOTES



- Ideal moisture content of wall should be below 12%
- The pH value of the wall must be between 7-11
- Keep the container tightly closed after use as Flexi Strong Acrylic Wall Putty dries up fast
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required
- Store away from edibles

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-1D, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

