

# FLEXI STRONG

CEMENT BASED WALL PUTTY



## PRODUCT DESCRIPTION

Macaw Flexi Strong Powder Putty is a cement-based wall putty with finest quality minerals, white cement and polymer. It fills the fine pores of the walls, removes surface unevenness and pinholes in plastered surfaces, thereby leaving behind a smooth and tough surface for painting. This putty can be applied over external or internal concrete/mortar substrates.

## USAGE AREA

- Perfect for application on new and old concrete/mortar/concrete plasters
- For application on painted surfaces, remove the old paint from surface using Emery paper or other suitable instruments
- Avoid applying on non-cemented surfaces

## SURFACE PREPARATION AND APPLICATION



- Before application of Macaw Flexi Strong Powder Putty remove all loose and flaky materials from the surfaces with Emery paper, putty blades, brush wires, etc.
- Clean the surface with soft cloth and ensure the surface is free from all loose dirt, dust, grease, fungi and algae
- Fill the hairline cracks and defects with good quality crack filler/cement according to the crack size and depth
- Apply Amendo Interior/Dura Fill Interior Primer on the surface, before and after the application of Macaw Flexi Strong Powder Putty
- Avoid adding putty into water bucket. It is always advised to add water in putty bucket to get a perfect blend. Mix the putty and water properly. Keep stirring till a smooth and even paste is formed. Use the water-putty paste within 5 hours to avoid the wastage as putty dries up fast



# FLEXI STRONG

CEMENT BASED WALL PUTTY



## APPLICATION PROCESS

- Follow bottom to upward direction, using putty blade/steel trowel to ensure less wastage and to get uniform and smooth finish
- After applying a coat of Macaw Flexi Strong Powder Putty, allow it to dry for 4-6 hours depending upon weather conditions
- After drying of the first coat, rub the surface very gently with putty blade. Use Emery paper to smooth loose particles, and allow it to dry
- Apply another coat of Macaw Flexi Strong Powder Putty once the first coat is fully dried
- Sand the surface properly with Emery paper
- Remove extra particles using soft sponge. Let the surface cure overnight for complete drying, before applying primer and paints

## STORAGE

- Store in a cool and dry shaded place away from sunlight
- Shelf life of 12 months from the date of manufacturing in original and sealed condition

## SAFETY, HEALTH AND ENVIRONMENT INFORMATION

- No added lead, mercury and chromium compound.
- During application and drying of the primer, ensure good ventilation and put on protective clothes
- The bag must be in a secure upright position and be tightly sealed
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required
- Store away from edibles and animals
- Do not use solvent or thinners
- Avoid pouring down the drain

## COMMODITY

Solid paint net quantity: 40 kg

**LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION**

\*T&C apply

### SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/II, Street No. 319, Action Area-1D, North 24 Parganas, New Town, Kolkata-700156, West Bengal

**For feedback/complaints, write to the customer care at the above address or call**

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

