

SHUDDHI

Acrylic Distemper



PRODUCT DESCRIPTION

Macaw Shuddhi Acrylic Distemper is a good-quality water-based distemper for interior walls. This value-for-money product comes with a matt finish and perfectly beautifies your home.

RECOMMENDED SURFACE

Plastered Surface

PRODUCT FEATURES



GOOD HIDING

The paint exhibits good hiding power, effectively concealing any underlying stains

TOXICITY



- Eco-friendly product with no added lead, mercury and chromium
- Low VOC

COLOUR RANGE

White and standard readymade colours available

COVERAGE (APPROX)



50-55 sq.ft./Kg/2 coats

- Coverage may depend on factors like surface conditions, surface preparations, application skills, weather conditions, dilution, etc.
- Coverage for darker shades may vary

FINISH

MATT

AVAILABLE PACKS



20kg



10kg



5kg



2kg



SHUDDHI

Acrylic Distemper



DIRECTIONS FOR APPLICATION

Application Method




Brush/Roller

Dilution Ratio



For brush application, add 200-300ml of potable water/kg of distemper

Recommended Undercoat



Flexi Strong Acrylic Wall Putty and Dura Fill Interior Primer

Drying Time




Keep 4-6 hours interval between two subsequent coats; allow complete drying of paint

SURFACE PREPARATION AND APPLICATION



- Before application ensure the surface is free from loose particles and dirt
- Wipe clean with dry cloth
- Apply first coat of Dura Fill Interior Primer on the walls; allow it to dry for 4 hours
- Apply Flexi Strong Acrylic Wall Putty and allow it dry for 4-6 hours
- Sand the surfaces with sandpaper no. 220 for smoothening
- Apply another coat of Dura Fill Interior Primer and allow sufficient drying time
- Apply 2-3 coats of Macaw Shuddhi Acrylic Distemper for best results. Keep 4-6 hours of drying time between coats

IMPORTANT NOTES



- Prior to use, stir the paint thoroughly
- Dilute the paint with potable water to the standard dilution up to 20-30% by volume
- Base material can be tinted with Macaw colour tinting machine, and needs to be mixed properly in gyro shaker
- Apply an additional coat for deeper shade
- Do not apply paint on lime-washed or damp surfaces
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-1D, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

