

CLIMATE CARE 4

ANTI-FUNGAL EXTERIOR EMULSION



PRODUCT DESCRIPTION

Climate Care 4 Anti-Fungal Exterior Emulsion is a water-based product. It provides superior protection to exterior walls along with a higher coverage and longer life than any ordinary emulsion.



PRODUCT FEATURES



4 YEARS PERFORMANCE WARRANTY

Enjoy three-year performance warranty on the quality and durability of Climate Care 3 Anti-Fungal Exterior Emulsion



GOOD HIDING

Climate Care 4 provides good hiding by covering all types of underlying stains



FUNGAL AND ALGAE PROTECTION

This exterior emulsion does not allow the growth of fungus and algae on the exterior walls

TOXICITY



- No added lead, mercury and chromium
- Low VOC

COVERAGE (APPROX)



50-55 sq.ft./L/2 coats

- Coverage may depend on factors like surface conditions, surface preparations, application skills, weather conditions, dilution, etc.
- Coverage for darker shades may vary

COLOUR RANGE



1000+ shades

FINISH

MATT

AVAILABLE PACKS



20 Ltr



10 Ltr



4 Ltr



1 Ltr

CLIMATE CARE 4

ANTI-FUNGAL EXTERIOR EMULSION



DIRECTIONS FOR APPLICATION

Application Method



Brush/Roller/Spray

Dilution Ratio



For brush application, add 400-500ml of potable water/L of emulsion. In case of dark bases, dilute as per requirement.

Recommended Undercoat



Dura Fill Exterior Primer

Drying Time




Surface Dry: 15-25 Minutes

Hard Dry: 4-6 Hours

*Drying time may vary as per weather conditions

SURFACE PREPARATION AND APPLICATION



- Before application ensure the surface is free from loose particles and dirt
- Wipe clean with dry cloth and ensure the surface is completely dry
- Fill the hairline cracks with good quality crack filler/cement
- Apply Dura Fill Exterior Primer on the surface and allow minimum 4 hours drying time
- Apply 2-3 coats of Climate Care 4 Anti-Fungal Exterior Emulsion for best results. Keep 4-6 hours of drying time between coats

IMPORTANT NOTES



- Prior to use, shake the container well
- Dilute the paint to the standard dilution up to 40-50% by volume. For deeper shade, dilute as per requirement
- After tinting the product with Macaw colour tinting machine, mix properly in gyro shaker
- Do not apply paint if the temperature is below 10°C or above 45°C
- Ideal moisture content of wall should be below 12%
- The pH value of the wall must be between 7-11
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata, West Bengal-700156

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

