

CLIMATE CARE Xtra Life 8

LUXURY EXTERIOR EMULSION



PRODUCT DESCRIPTION

Climate Care Xtra Life 8 is a premium quality luxury exterior emulsion that provides extended life and protection to your walls from damaging effects of harsh weather conditions, algae and fungi. The paint has silicon reinforced polymer composition that guarantees good water repellent property and ensures long-lasting wall freshness. The emulsion also comes with a 8-year performance warranty.

PRODUCT FEATURES



RICH SHEEN

Its sheen finish brings out the mystic beauty of exterior walls



WATER RESISTANT

It resists damaging of exterior walls in heavy rains and harsh weather



HIGHLY FLEXIBLE

Does not allow bents and cracks in the paint



FUNGUS & ALGAE PROTECTION

Climate Care Xtra Life 8 Luxury Exterior Emulsion helps resist any formation of fungus & algae on the exterior walls

TOXICITY



- No added lead, mercury and chromium
- Low VOC

COLOUR RANGE



1000+ shades

FINISH

SMOOTH AND RICH SHEEN

COVERAGE (APPROX)



55-60 sq.ft./L/2 coats

- Coverage may depend on factors like surface conditions, surface preparation, application skills, weather conditions, dilution etc.
- Coverage for darker shades may vary

AVAILABLE PACKS



20 Ltr



10 Ltr



4 Ltr



1 Ltr



CLIMATE CARE Xtra Life 8

LUXURY EXTERIOR EMULSION



DIRECTIONS FOR APPLICATION

Application Method



Brush/Roller/Spray

Dilution Ratio



For brush application, add 400-500ml of potable water/L of emulsion.

Recommended Undercoat



Amendo Alkali-Block Exterior Primer

Drying Time



Surface Dry: 15-25 minutes

Hard Dry: 4-6 Hours

*Drying time may vary as per weather conditions

SURFACE PREPARATION AND APPLICATION



- Before application ensure the surface is free from loose particles and dirt
- Wipe clean with dry cloth and ensure the surface is completely dry
- Fill the hairline cracks with good quality crack filler/cement
- Apply Amendo Alkali-Block Exterior Primer on the surface, and allow minimum 4 hours drying time
- Apply 2-3 coats of Climate Care Xtra Life 8 Luxury Exterior Emulsion for best results. Keep 4-6 hours of drying time between coats

IMPORTANT NOTES



- Prior to use, shake the container well
- Dilute the paint to the standard dilution up to 40-50% by volume. For deeper shade, dilute as per requirement
- After tinting the product with Macaw colour tinting machine, mix properly in gyro shaker
- Do not apply paint if the temperature is below 10°C or above 45°C
- Ideal moisture content of wall should be below 12%
- The pH value of the wall must be between 7-11
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required

CLEANING POST PAINT

- Use 2-3% of mild soap solution in water to remove stains from painted walls
- Slowly splash water to remove the dust and dirt

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

