

AURA CLEAN

LUXURY INTERIOR EMULSION



PRODUCT DESCRIPTION

Aura Clean Luxury Interior emulsion is designed with advanced co-polymers that make your walls resistant to stains. It provides high washability and ensures the walls remain fresh and pristine for a longer period.

PRODUCT FEATURES



MICRO CROSS-LINKING

The unique polymers in Aura Clean make it easily washable and create a protective barrier that prevents stains, ensuring effortless cleaning



EASILY WASHABLE

The paint can be easily washed and it retains the freshness for an extended period



STAIN RESISTANT

Prevents stains from adhering to painted walls

TOXICITY



- No added lead, mercury and chromium
- Low VOC

COVERAGE (APPROX)



130-140 sq.ft./L/2 coats

- Coverage may depend on factors like surface conditions, surface preparations, application skills, weather conditions, dilution, etc.
- Coverage for darker shades may vary

COLOUR RANGE



1000+ shades

FINISH

SMOOTH

AVAILABLE PACKS



20 Ltr



10 Ltr



4 Ltr



1 Ltr



AURA CLEAN

LUXURY INTERIOR EMULSION



DIRECTIONS FOR APPLICATION

Application Method



Brush/Roller/Spray

Dilution Ratio



For brush application, add 400-500ml of potable water/L of emulsion. In case of dark bases, dilute as per requirement.

Recommended Undercoat



Flexi Strong Acrylic Wall Putty
and
Amendo Interior Primer

Drying Time



Surface Dry: 15-25 minutes

Hard Dry: 4-6 Hours

*Drying time may vary as per weather conditions

DIRECTIONS FOR USE

SURFACE PREPARATION AND APPLICATION



- Before application ensure the surface is free from loose particles and dirt
- Wipe clean with dry cloth and ensure the surface is completely dry
- Apply Amendo Interior Primer on the surface, and allow minimum 4 hours drying time
- Apply Flexi Strong Acrylic Wall Putty to cover hairline cracks and uneven surfaces; allow it to dry completely
- Sand the surfaces with sandpaper no. 220 or 320 for smoothening, apply another coat of primer; allow sufficient drying time
- Apply 2-3 coats of Aura Clean Luxury Interior Emulsion for best results. Keep 4-6 hours of drying time between coats

IMPORTANT NOTES



- Prior to use, shake the container well
- Dilute the paint with potable water to the standard dilution up to 40-50% by volume. For deeper shade, dilute as per requirement
- After tinting the product with Macaw colour tinting machine, mix properly in gyro shaker
- Do not apply paint if the temperature is below 10°C or above 45°C
- Ideal moisture content of wall should be below 12%
- The pH value of the wall must be between 7-11
- Avoid leaving diluted emulsion exposed for a long time
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM



SHYAM STEEL
SINCE 1953