

AURA SHINE

LUXURY INTERIOR EMULSION



PRODUCT DESCRIPTION

Aura Shine Luxury Interior Emulsion defines the aesthetic of your home and gives your interior walls a glowing and silky finish. It is a stain resistant product with high resilience and enduring life span.

PRODUCT FEATURES



SILK FINISH

Finely ground particles in paint enhance the painting process, enabling smoother brush application and resulting in a silky finish



SUPERIOR SHEEN

The glowing appearance enhances the aesthetic appeal of the interior walls



STAIN RESISTANT

Prevents stains from adhering to painted walls



HIGHLY WASHABLE

The paint is highly washable and remains fresh and clean for a long time

TOXICITY



- No added lead, mercury and chromium
- Low VOC

COVERAGE (APPROX)



130-140 sq.ft./L/2 coats

- Coverage may depend on factors like surface conditions, surface preparations, application skills, weather conditions, dilution, etc.
- Coverage for darker shades may vary

COLOUR RANGE



1000+ shades

FINISH

SMOOTH

AVAILABLE PACKS



20 Ltr



10 Ltr



4 Ltr



1 Ltr



AURA SHINE

LUXURY INTERIOR EMULSION



DIRECTIONS FOR APPLICATION

Application Method



Brush/Roller/Spray

Dilution Ratio



For brush application, add 400-500ml of potable water/L of emulsion. In case of dark bases, dilute as per requirement.

Recommended Undercoat



Flexi Strong Acrylic Wall Putty and Amendo Interior Primer

Drying Time



Surface Dry: 15-25 minutes

Hard Dry: 4-6 Hours

*Drying time may vary as per weather conditions

SURFACE PREPARATION AND APPLICATION



- Before application ensure the surface is free from loose particles and dirt
- Wipe clean with dry cloth and ensure the surface is completely dry
- Apply Amendo Interior Primer on the surface, and allow minimum 4 hours drying time
- Apply Flexi Strong Acrylic Wall Putty to cover hairline cracks and uneven surfaces; allow it to dry completely
- Sand the surfaces with sandpaper no. 220 or 320 for smoothening, apply another coat of primer; allow sufficient drying time
- Apply 2-3 coats of Aura Shine Luxury Interior Emulsion for best results. Keep 4-6 hours of drying time between coats

IMPORTANT NOTES



- Prior to use, shake the container well
- Dilute the paint with potable water to the standard dilution up to 40-50% by volume. For deeper shade, dilute as per requirement
- After tinting the product with Macaw colour tinting machine, mix properly in gyro shaker
- Do not apply paint if the temperature is below 10°C or above 45°C
- Ideal moisture content of wall should be below 12%
- The pH value of the wall must be between 7-11
- Avoid leaving diluted emulsion exposed for a long time
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM



SHYAM STEEL
SINCE 1953