

DURA SMOOTH

INTERIOR ACRYLIC EMULSION



PRODUCT DESCRIPTION

Dura Smooth Interior Acrylic Emulsion offers a wide range of colours, better coverage, durability and smoothness in comparison to any ordinary emulsion.

PRODUCT FEATURES



GOOD HIDING

The paint exhibits good hiding power, effectively concealing any underlying paints



HIGH COVERAGE

This product has higher coverage than any ordinary emulsion



EASY TO APPLY

Compared to any ordinary emulsion, Dura Smooth is very easy to use and apply



LONGER LIFE

The acrylic emulsion has a prolonged lifespan, ensuring long-lasting durability

TOXICITY



- Eco-friendly product with no added lead, mercury and chromium
- Low VOC

COLOUR RANGE



1000+
shades

FINISH

MATT

COVERAGE (APPROX)



80-90 sq.ft./L/2 coats

- Coverage may depend on factors like surface conditions, surface preparations, application skills, weather conditions, dilution, etc.
- Coverage for darker shades may vary

AVAILABLE PACKS



20 Ltr



10 Ltr



4 Ltr



1 Ltr



DURA SMOOTH

INTERIOR ACRYLIC EMULSION



DIRECTIONS FOR APPLICATION

Application Method



Brush/Roller/Spray

Dilution Ratio



For brush application, add 400-500ml of potable water/L of emulsion. In case of dark bases, dilute as per requirement.

Recommended Undercoat



Flexi Strong Acrylic Wall Putty and Dura Fill Interior Primers

Drying Time




Surface Dry: 15-25 minutes

Hard Dry: 4-6 Hours

*Drying time may vary as per weather conditions

SURFACE PREPARATION AND APPLICATION



- Before application ensure the surface is free from loose particles and dirt
- Wipe clean with dry cloth and ensure the surface is completely dry
- Apply Dura Fill Interior Primer on the surface, and allow minimum 4 hours drying time
- Apply Flexi Strong Acrylic Wall Putty to cover hairline cracks and uneven surfaces; allow it to dry completely
- Sand the surfaces with sandpaper no. 220 or 320 for smoothening, apply another coat of primer; allow sufficient drying time
- Apply 2-3 coats of Dura Smooth Interior Acrylic Emulsion for best results. Keep 4-6 hours of drying time between coats

IMPORTANT NOTES



- Prior to use, shake the container well
- Dilute the paint with potable water to the standard dilution up to 40-50% by volume. For deeper shade, dilute as per requirement
- After tinting the product with Macaw colour tinting machine, mix properly in gyro shaker
- Do not apply paint if the temperature is below 10°C or above 45°C
- Ideal moisture content of wall should be below 12%
- The pH value of the wall must be between 7-11
- Avoid leaving diluted emulsion exposed for a long time
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-ID, North 24 Parganas, New Town, Kolkata, West Bengal-700156

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

